



SAFETY DATA SHEET

187666 A7691 EVVA MULTISPRAY 200ML

Page 1

Issued: 02.06.2008

Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: 187666 A7691 EVVA MULTISPRAY 200ML
Product code: 74 2546
Company name: EVVA-WERK GmbH&Co.KG
Wienerbergstrasse 59-65
A-1120 Wien
Österreich
Tel: +43-1811-65-0
Fax: +43-1812-2071
Email: verkauf@evva.com

2. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.
Other hazards: Extremely flammable. In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: NAPHTHA (ERDÖL), MIT WASSERSTOFF BEHANDELTE LEICHTE ; NAPHTHA, WASSERSTOFFBEHANDELT, NIEDRIG SIEDEND (5) 30-50%
EINECS: 265-151-9 CAS: 64742-49-0
[F] R11; [Xi] R38; [N] R51/53; [Xn] R65; [-] R67

- PROPAN 1-10%
EINECS: 200-827-9 CAS: 74-98-6
[F+] R12
- BUTAN 20-30%
EINECS: 203-448-7 CAS: 106-97-8
[F+] R12
- ISOBUTAN 1-10%
EINECS: 200-857-2 CAS: 75-28-5
[F+] R12

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: Headaches or general malaise may result.
Inhalation: Drowsiness or mental confusion may occur.

4. FIRST AID MEASURES (ACTION)

Skin contact: Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

[cont...]

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder.

Exposure hazards: Forms explosive air-vapour mixture. Extremely flammable.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Mechanically ventilate the spillage area whilst avoiding the formation of explosive concentrations - see section 9 of SDS.

Environmental precautions: Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes or gas.

Clean-up procedures: Absorb into dry earth or sand.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.

Storage conditions: Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: NAPHTHA (ERDÖL), MIT WASSERSTOFF BEHANDELTE LEICHTE ; NAPHTHA, WASSERSTOFFBEHANDELT, NIEDRIG SIEDEND (5)

WEL (8 hr exposure limit): 200 ppm

- PROPAN

WEL (8 hr exposure limit): 1000 ppm

- BUTAN

WEL (8 hr exposure limit): 1000 ppm

- ISOBUTAN

WEL (8 hr exposure limit): 1000 ppm

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Nitrile gloves. Breakthrough time of the glove material > 8 hours.

Eye protection: Safety goggles.

Skin protection: Solvent resistant protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES**State:** Aerosol**Colour:** Pale yellow**Odour:** Characteristic odour**Evaporation rate:** Fast**Solubility in water:** Insoluble**Flammability limits %: lower:** 1,4**upper:** 32,0**Flash point°C:** -60**Autoflammability°C:** 510**Vapour pressure:** 3200 hPa**Relative density:** 0,66 g/ml**VOC g/l:** 572**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Sources of ignition. Heat.**Materials to avoid:** Oxidising agents.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.**11. TOXICOLOGICAL INFORMATION****Chronic toxicity:** Danger of serious damage to health by prolonged exposure through inhalation. Danger of serious damage to health by prolonged exposure in contact with skin.**12. ECOLOGICAL INFORMATION****Mobility:** Highly volatile. Vapour is heavier than air.**Persistence and degradability:** Not biodegradable.**Bioaccumulative potential:** No data available.**Other adverse effects:** Toxic to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D1 Tipping above or underground (e.g. landfill, etc.).

R3 Recycling/reclamation of metals and metal compounds.

Waste code number: 150110, 150104**Disposal of packaging:** Dispose of as normal industrial waste.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1950

ADR Class: 2

Classification code: 5F

Shipping name: AEROSOLS

Labelling: 2.1

**IMDG / IMO**

UN no: 1950

Class: 2

EmS: F-D,S-U

Marine pollutant: .

Labelling: 2.1

IATA / ICAO

UN no: 1950

Class: 2

Labelling: 2.1

15. REGULATORY INFORMATION**Hazard symbols:** Extremely flammable.

Irritant.

Dangerous for the environment.

**Risk phrases:** R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S23: Do not breathe aerosol.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

[cont...]

Seveso II guideline: Yes

Water hazard class: 1 Classification by VwVwS

Air emission directive: Item no: 5.2.5 Amount m%: 87

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: Storage classification 2B

Limited Quantities.

AOX. no.

Safety Data Sheet according to Regulation (EU) No. 1907/2006

Risk phrases used in s.3: R11: Highly flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R67: Vapours may cause drowsiness and dizziness.

R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.